

Amendments to the Claims

The following listing of claims replaces all prior versions and listings of claims in this patent application:

Listing of Claims

1. (Currently amended) A method for forming a fuel cell assembly, comprising the steps of:
 - a) forming a fuel cell sub-assembly module containing at least two bonded together fuel cell units, said at least two fuel cell units each including an anode, a cathode, and a membrane electrode assembly, wherein said at least two fuel cell units are bonded together using at least one elastomeric gasket and at least one gasketing element, and wherein one of said at least one elastomeric gasket or said at least one gasketing element is cured prior to bonding together said at least two fuel cell units, and the other of said at least one elastomeric gasket and said at least one gasketing element is cured during the bonding together of said at least two fuel cell units;
 - b) testing said sub-assembly module; and
 - c) joining together a plurality of sub-assembly modules to form said fuel cell assembly.
2. (Cancelled).

3. (Original) A method in accordance with Claim 1 wherein each of said sub-assembly modules comprises a plurality of bipolar plates assemblies interspersed with a plurality of membrane electrode assembly elements.

4. (Currently amended) A method in accordance with Claim 1 wherein said forming step for each of said sub-assembly modules includes the steps of:

a) providing an assembly fixture having at least one alignment element for receiving fuel cell components:

b) selecting $n+1$ number of bipolar plate assemblies and n number of membrane electrode assembly elements, each bipolar plate assembly having an anode and a cathode, wherein n is the number of said plurality of fuel cell units desired in said sub-assembly module;

c) providing an said at least one elastomeric gasket on one of said anode and cathode of $n+1$ bipolar plate assemblies;

d) providing a said at least one gasketing element on the other of said anode and said cathode of $n+1$ bipolar plate assemblies, at least one of said at least one elastomeric gasket and said at least one gasketing element including a curable liquid rubber material;

e) installing onto said assembly fixture one of said $n+1$ bipolar plate assemblies, said alignment element engaging said one of said $n+1$ bipolar plate assemblies;

f) installing onto said assembly fixture a membrane electrode assembly element into contact with said just-installed bipolar plate assembly;

g) installing onto said assembly fixture another of said **n+1** bipolar plate assemblies, the anode of said one or said another of said **n+1** bipolar plate assemblies being disposed adjacent said cathode of the other of said one or said another of said **n+1** bipolar plate assemblies, and said alignment element engaging said bipolar plate assembly being installed;

h) repeating steps f) and g) for the remaining number of provided bipolar plate assemblies and provided MEA elements to form a stack of **n** fuel cell units;

i) applying compressive force to said stack of **n** fuel cell units whilst curing said curable liquid rubber material of said at least one of said elastomeric gasket and said at least one gasketing element to form a fuel cell sub-assembly module.

5. (Cancelled).

6. (Cancelled).

7. (Currently amended) A method in accordance with Claim 4 wherein said at least one elastomeric gasket includes a sealant that is liquid during said bipolar plate installing step.

8. (Currently amended) A method in accordance with Claim 4 wherein said at least one gasketing element includes a sealant that is liquid during said bipolar plate installing step.

9. (Original) A method in accordance with Claim 4 wherein at least one of said membrane electrode assemblies includes gas diffusion layers.

Claims 10-13 (Cancelled).

14. (Previously presented) A fuel cell assembly comprising a plurality of fuel cells bonded together to form a fuel cell sub-assembly module, wherein said fuel cell sub-assembly module is included in a plurality of fuel cell sub-assembly modules, wherein said plurality of fuel cell sub-assembly modules are bonded together to form said fuel cell assembly, wherein at least one of said fuel cells includes a bipolar plate assembly and a membrane electrode assembly, wherein at least one gasket and at least one gasketing element are positioned between at least two of said plurality of fuel cells, and wherein one of said at least one gasket or said at least one gasketing element is cured prior to bonding together said at least two of said plurality of fuel cells, and the other of said at least one gasket and said at least one gasketing element is cured during the bonding together of said at least two of said plurality of fuel cells.

15. (Cancelled).

16. (Cancelled).

17. (Previously presented) A fuel cell assembly comprising a plurality of fuel cells bonded together to form a fuel cell sub-assembly module, wherein said fuel cell sub-assembly module is included in a plurality of fuel cell sub-assembly modules, wherein said plurality of fuel cell sub-assembly modules are bonded together to form said fuel cell assembly, wherein at least one of said fuel cells includes a bipolar plate assembly and a membrane electrode assembly, wherein at least one gasket and at least one gasketing element are positioned between each at least two of said plurality of fuel cell sub-assembly modules, and wherein one of said at least one gasket or said at least one gasketing element is cured prior to bonding together said at least two of said fuel cell sub-assemblies, and the other of said at least one gasket and said at least one gasketing element is cured during the bonding together of said at least two of said fuel cell sub-assembly modules.

18. (Cancelled).

19. (Cancelled).

20. (Previously presented) A method in accordance with Claim 4 wherein said at least one alignment element is a rod, wherein each of said bipolar plate assemblies include a bore, and wherein each of said bores receive said rod to align said bipolar plate assemblies.

21. (Cancelled).

22. (Currently amended) A method in accordance with Claim 24 1
wherein said at least one gasketing element has a thickness of no more than about
.005 inches.

23. (Currently amended) A method ~~in accordance with Claim 19~~ for
forming a fuel cell assembly, comprising the steps of:

a) forming a fuel cell sub-assembly module containing at least two bonded
together fuel cell units, said at least two fuel cell units each including an anode, a
cathode, and a membrane electrode assembly;

b) testing said sub-assembly module; and

c) joining together a plurality of sub-assembly modules to form said fuel cell
assembly, wherein said plurality of sub-assembly modules are joined together using
at least one elastomeric gasket and at least one gasketing element, and wherein
one of said at least one elastomeric gasket or said at least one gasketing element is
cured prior to joining together at least two of said plurality of sub-assembly modules,
and the other of said at least one elastomeric gasket and said at least one gasketing
element is cured during the joining together of said at least two of said plurality of
sub-assembly modules.

24. (Previously presented) A method in accordance with Claim 23
wherein said at least one gasketing element has a thickness of no more than about
.005 inches.

25. (Previously presented) A fuel cell assembly in accordance with Claim 14 wherein said at least one gasketing element has a thickness of no more than about .005 inches.

26. (Previously presented) A fuel cell assembly in accordance with Claim 14 wherein said membrane electrode assembly is positioned between at least one of said at least one gasket and said at least one gasketing element.

27. (Previously presented) A fuel cell assembly in accordance with Claim 17 wherein said at least one gasketing element has a thickness of no more than about .005 inches.

28. (Previously presented) A fuel cell assembly in accordance with Claim 17 wherein said membrane electrode assembly is positioned between at least one of said at least one gasket and said at least one gasketing element.